## 13.3" P-cap Touch Screen Monitor

Interact with Ideas



## **Features**

- > Designed by Horsent, Thin body for generous smart display
- > Open-frame, Special designed front slim bezel
- > Capacitive 10 points sensitive touchscreen technology
- > Vivid LED Backlight with 16.7 million color
- > Durable and reliable
- > Cost-competitive
- > Standard Brightness: 300 nit
- > Supported for Windows 11

## **Applications**


- > Interactive Ads
- > Commercial & Retail

- > Presentation
- > Self-service



## **Specifications**

Product Name		13.3 inch P-cap Touch Screen Monitor		
Product Model		H1312P-UH		
	Size	13.3inch		
LCD Panel	Aspect Ratio	16:9		
	Backlight	LED		
	Pixel Pitch	0.1529mm x 0.1529mm		
	Active Area	Horizontal: 293.76mm Vertical: 165.24mm		
	Best Resolution	1920 x 1080 @ 60Hz		
	Response Time	25ms		
	Colors	16.7 million		
LCD Farier	Brightness	300nit		
	Contrast Ratio	800:1 (Standard Value)		
	Viewing Angle (CR > 10)	Horizontal: 170° (85°/85°) Vertical: 160° (85°/85°)		
	Video Input Format	RGB Analog Signal/ Digital Signal		
	Video Input Interface	VGA/HDMI		
	Input Frequency	Horizontal: 30~82Hz Vertical:60~75Hz		
	Power Consumption	≤6W		
	Touch Screen Type	Capacitive Touch Screen		
	Cover Glass	2.4mm		
	Transparency	87%		
Touch Screen	Hardness	7H		
Touch Screen	Interface	USB2.0		
	Touch Point	10		
	Response Time	≤15 ms		
	Touch Method	Finger / Capacitive Pen		
	Touch Lifespan	≥50,000,000 times		
	Single-point OS	Windows 7,8,10, Linux		
	Multi-point OS	Windows 10,11, Android 7 and later		
	Dimension	326.0mm x 210.0mm x 36.0mm		
	OSD Panel	Power Switch, Menu, Up, Auto, Down		
	Power Supply	Input: DC 12V ± 5%		
	Power Consumption	Max: 12W		
Overview	Installation	Rear Mount(Side and VESA Mount 75mmx75mm)		
	Accessory	Power Line 1.5m, CCC / EU / US / UK standard, Black(Optional)		
		Signal Line VGA, HDMI, male to male, 1.5m, Black(Optional)		
		USB Wire A male to B male, 1.8m  External Adapter: WT1203000, 12V/3.0A, 115mm x 47mm x 31mm		
		Length: 1.0m, ¢ 2.5 , Black		
	Temperature	Operating: 0°C-40°C; Storage: -20°C-60°C		
	Humidity Operation Altitude	Operating: 20%-80%; Storage: 10%-90% < 3000m		
	Operation Altitude MTBF			
	Net Weight	50,000 hours demonstrated		
		2.45kg		
	Agency Approvals	CCC, FCC, CE, RoHS		
	Warranty	1 Year		



DIMENSIONS ARE IN MILLIMETERS

Tolerance: ±1.0mm			DATE: 2021.03.03		
SHEET	1	OF	1	REV: V0.1	