15.6" P-cap Touch Screen Monitor

Interact with Ideas



Features

- > Designed by Horsent, Thin body for generous smart display
- > Open-frame, Special designed front slim bezel
- > Capacitive 10 points sensitive touchscreen technology
- > Vivid FHD LED Backlight with 16.7 million color
- > Durable and reliable
- > Cost-competitive
- > Standard Brightness: 300 nit
- > Supported for Windows 11

Applications

- > Interactive Ads
- > Commercial & Retail

- > Presentation
- > Self-service



Specifications

| Product Name | | 15.6 inch P-cap Touch Screen Monitor |
|---------------|-------------------------|---|
| Product Model | | H1512PWH-UH |
| LCD Panel | Size | 15.6inch |
| | Aspect Ratio | 16:9 |
| | Backlight | LED |
| | Pixel Pitch | 0.252mm x 0.252mm |
| | Active Area | Horizontal: 344.16mm Vertical: 193.59mm |
| | Best Resolution | 1920 x 1080 @ 60Hz |
| | Response Time | 30ms |
| | Colors | 16.7 million |
| | Brightness | 300nit |
| | Contrast Ratio | 700:1 (Standard Value) |
| | Viewing Angle (CR > 10) | Horizontal: 170° (85°/85°) Vertical: 170° (85°/85°) |
| | Video Input Format | RGB Analog Signal/ Digital Signal |
| | Video Input Interface | VGA/HDMI |
| | Input Frequency | Horizontal: 30~82Hz Vertical:50~75Hz |
| | Power Consumption | ≤12W |
| Touch Screen | Touch Screen Type | Capacitive Touch Screen |
| | Cover Glass | 2.4mm |
| | Transparency | 87% |
| | Hardness | 7H |
| | Interface | USB2.0 |
| | Touch Point | 10 |
| | Response Time | ≤10 ms |
| | Touch Method | Finger / Capacitive Pen |
| | Touch Lifespan | ≥50,000,000 times |
| | Single-point OS | Windows 7,8,10, Linux |
| | Multi-point OS | Windows 10,11, Android 7 and later |
| Overview | Dimension | 382mm x 248mm x 44.5mm |
| | OSD Panel | Power Switch, Menu, Up, Auto, Down |
| | Power Supply | Input: DC 12V ± 5% |
| | Power Consumption | Max: 20W, Sleep: 2W, Off: 1W |
| | Installation | Rear Mount(Side and VESA Mount 75mmx100mm) |
| | Accessory | Power Line 1.5m, CCC / EU / US / UK standard, Black(Optional) |
| | | Signal Line VGA, HDMI, male to male , 1.5m, Black(Optional) |
| | | USB Wire A male to B male, 1.8m |
| | | External Adapter: WT1203000, 12V/3.0A, 115mm x 47mm x 31mm |
| | | Length: 1.0m, ¢ 2.5 , Black |
| | Temperature | Operating: 0°C-40°C; Storage: -20°C-60°C |
| | Humidity | Operating: 20%-80%; Storage: 10%-90% |
| | Operation Altitude | <3000m |
| | MTBF | 50,000 hours demonstrated |
| | Net Weight | 3.5kg |
| | Agency Approvals | CCC, FCC, CE, RoHS |
| | Warranty | 1 Year |



