

17" P-cap Touch Screen Monitor

Interact with Ideas



Features

- > Designed by Horsent, Ultral-thin body for generous smart display
- > Zero bezel, VESA wall mount and support desktop stand
- > Capacitive 10 points sensitive touchscreen technology
- > Vivid FHD LED Backlight with 16.7 million color
- > Durable and reliable
- > Cost-competitive
- > Standard Brightness: 250 nit
- > Supported for Windows 11

Applications

- > Interactive Ads
- > Commercial & Retail
- > Presentation
- > Self-service

Specifications

Product Name		17 inch P-cap Touch Screen Monitor	
Product Model		H1716P-UH	
LCD Panel	Size	17inch	
	Aspect Ratio	5:4	
	Backlight	LED	
	Pixel Pitch	0.246mm x 0.246mm	
	Active Area	Horizontal: 337.92mm Vertical: 270.336mm	
	Best Resolution	1280 x 1024 @ 60Hz	
	Response Time	5ms	
	Colors	16.7 million	
	Brightness	250nit	
	Contrast Ratio	1000:1 (Standard Value)	
	Viewing Angle (CR > 10)	Horizontal: 170° (85°/85°) Vertical: 160° (80°/80°)	
	Video Input Format	RGB Analog Signal/ Digital Signal	
	Video Input Interface	VGA/HDMI	
	Input Frequency	Horizontal: 30~82Hz Vertical:50~75Hz	
Power Consumption	≤12W		
Touch Screen	Touch Screen Type	Capacitive Touch Screen	
	Cover Glass	2mm	
	Transparency	87%	
	Hardness	7H	
	Interface	USB2.0	
	Touch Point	10	
	Response Time	≤10 ms	
	Touch Method	Finger / Capacitive Pen	
	Touch Lifespan	≥50,000,000 times	
	Single-point OS	Windows 7,8,10, Linux	
	Multi-point OS	Windows 10,11, Android 7 and later	
Overview	Dimension	389.1mm x 321.5mm x 38.8mm	
	OSD Panel(Optional)	Power Switch, Menu, Up, Auto, Down	
	Power Supply	Input: DC 12V ± 5%	
	Power Consumption	Max: 20W	
	Installation	Wall Mount VESA 75mm x 75mm	
	Accessory	Power Line	1.5m, CCC / EU / US / UK standard, Black(Optional)
		Signal Line	VGA, HDMI, 1.5m/1.8m, male to male(Optional)
		USB Wire	A male to B male, 1.8m
		External Adapter: WT1203000, 12V/3.0A, 115mm x 47mm x 31mm Length: 1.0m, ϕ 2.0 , Black	
	Temperature	Operating: 0°C-40°C; Storage: -20°C-60°C	
	Humidity	Operating: 20%-80%; Storage: 10%-90%	
	Operation Altitude	< 3000m	
	MTBF	50,000 hours demonstrated	
	Net Weight	4.3kg	
Agency Approvals	CCC, FCC, CE, RoHS		
Warranty	1 Year		

