

# 17" P-cap Thin Touch Monitor



**Model** **H1716P-UH**

---

**Touch Technology** **P-cap**

---

**Version** **V 1.0**

---

Product Name		17 inch LCD Thin Touch Monitor		
Product Model		H1716P-UH		
LCD panel Technical Parameter	Size	17inch		
	Aspect Ratio	5 : 4		
	Backlight Type	LED Backlight		
	Pixel Pitch	0.246mm x 0.246mm		
	Active Area	337.92mm*270.336mm		
	Best Resolution	1280 × 1024@ 60 Hz		
	Response Time	5 ms		
	Color	16.7 million		
	Brightness	LCD Panel: 250 cd/m <sup>2</sup>		
	Contrast Ratio	1000:1 (standard Values)		
	Viewing Angle (CR > 10)	Horizontal: 170° (85°/85°)    Vertical: 160° (80°/80°)		
	Video Input Format	RGB Analog Signal/ Digital Signal		
	Video Input Interface	VGA / HDMI		
	Input Frequency	Horizontal: 30~82 Hz    Vertical: 50~75 Hz		
	Power Consumption	≤12W		
	Warranty	1 Year		
Touch Screen Technical Parameter	Touch Screen Type	Capacitive Touch Screen		
	Cover Glass	2mm		
	Transparency	87%		
	Hardness	7H		
	Interface	USB2.0		
	Touch Point	10		
	Response Time	≤10 ms		
	Touch Method	Finger / Capacitive Pen		
	Touch Lifespan	≥50,000,000		
	Linearity	< 2%		
	Single-point OS	Windows XP , Linux		
	Multi-points OS	Windows7/8/10 , Android		
	Warranty	1 Year		
	Touch Monitor Technical Parameter	Boundary Dimension	389.1mm × 321.5mm × 38.8mm	
OSD Panel		Optional Accessory : Power switch、Menu、Up、Auto、Down		
Power Supply		Input : DC 12V±5%		
Power Consumption		Max : 20w		
Installation		VESA 75mm		
Accessory (Optional)		Signal Line	VGA/HDMI, 1.8m, male to male	
		USB Wire	A male to B male , 1.8m	
		Adaptor	WT1203000 , 12V/3.0A , 115mmx47mmx31mm , Length 1.0m , φ 2.0 , Black	
		Power Line	Power Line, 1.5m , Black	
Temperature		Operating: 0°C-40°C ;    Storage: -20°C-60°C		
Humidity		Operating: 20%-80%;    Storage: 10%-90%		
Operation Altitude		< 3000m		
Warranty		1 Year		

