## 43" P-cap Touch Screen Monitor

Interact with Ideas



## **Features**

- > Designed by Horsent, thin body for generous smart display
- > Open-frame, Special designed front slim bezel
- > Capacitive 10 points sensitive touchscreen technology
- > Vivid 4K UHD LED Backlight with 16.7 million color
- > Durable and reliable
- > Cost-competitive
- > Standard Brightness: 500 nit
- > Supported for Windows 11

## **Applications**


- > Interactive Ads
- > Commercial & Retail


- > Presentation
- > Self-service




## **Specifications**

Product Name		43 inch P-cap Touch Screen Monitor		
Product Model		H4312PK-UH		
	Size	43inch		
	Aspect Ratio	16:9		
	Backlight	LED		
	Pixel Pitch	0.2451mm x 0.2451mm		
	Active Area	Horizontal: 941.184mm Vertical: 529.416mm		
	Best Resolution	3840 x 2160 @ 60Hz		
	Response Time	10ms		
LOD Damel	Colors	16.7 million		
LCD Panel	Brightness	500nit		
	Contrast Ratio	1200:1 (Standard Value)		
	Viewing Angle (CR > 10)	Horizontal: 178° (89°/89°) Vertical: 178° (89°/89°)		
	Video Input Format	Digital Signal		
	Video Input Interface	DP/HDMI		
	Input Frequency	Horizontal: 30~82Hz Vertical:50~75Hz		
	Power Consumption	≤85W		
	Touch Screen Type	Capacitive Touch Screen		
	Cover Glass	3mm Chemical Strengthen		
	Transparency	87%		
Touch Screen	Hardness	7H		
Touch Screen	Interface	USB2.0		
	Touch Point	10		
	Response Time	≤10 ms		
	Touch Method	Finger / Capacitive Pen		
	Touch Lifespan	≥50,000,000 times		
	Single-point OS	Windows 7,8,10, Linux		
	Multi-point OS	Windows 10,11, Android 7 and later		
	Dimension	1011.10mm x 599.30mm x 64.6mm		
	OSD Panel	Power Switch, Menu, Up, Auto, Down		
Overview	Power Supply	Input: AC 220V ± 5%		
	Power Consumption	Max: 95W		
	Installation	Rear Mount(Side and VESA Mount 400mm x 400mm)		
	Accessory	Power Line 1.5m, CCC / EU / US / UK standard, Black(Optional)		
		Signal Line HDMI,1.8m, male to male, Black(Optional)		
	Tanananahana	USB Wire A male to B male, 1.8m		
	Temperature	Operating: 0°C-40°C; Storage: -20°C-60°C		
	Humidity Operation Altitude	Operating: 20%-80%; Storage: 10%-90%		
	Operation Altitude MTBF	< 3000m  50,000 hours domonstrated		
		50,000 hours demonstrated		
	Net Weight	23.3kg		
	Agency Approvals	CCC, FCC, CE, RoHS		
	Waterproof	Front IP65		
	Warranty	1 Year		







Tolerance: ±1.0mm				DATE: 2022.06.28	
SHEET	1	OF		REV: V0.1	