

# 43 " 4K P-cap Openframe Touch Screen

Model	H4314PK-UH
-------	------------

Touch Technology	P-cap
------------------	-------

Version	V 1.0
---------	-------



---

## We Make it Clear

### 4K resolution for more details

By almost 4 times of pixel,

your audience is able to see more details of your Ads items

DP and 2HDMI, 2USB and USB type B, you will enjoy the vivid display by more options

We upgrade to 500 nits to make your media more visible even near the window

you can make your kiosk or interactive media an attractive site to have its own fans.

Users' vision in 16.7 million of colour and operations are primarily upgraded and developed to a new degree of interaction.

- 10-point touch
- IP 65 Front
- Slim bezel
- Firm sealing
- Accurate touch
- 4K resolution
- Easy to install
- Flush mounted

- ATM
- Tickets machine
- Vending machine
- Information terminal
- Gaming machine



## Product specification

Product Name		43 inch LCD Touch Monitor	
Product Model		H4314PK-UH	
LCD panel Technical Parameter	Size	43 inch	
	Aspect Ratio	16 : 9	
	Backlight Type	LED Backlight	
	Pixel Pitch	0.2451mm x 0.2451mm	
	Active Area	941.184mm *529.416mm	
	Best Resolution	3840 × 2160 @ 60 Hz	
	Response Time	10 ms	
	Color	16.7 million	
	Brightness	LCD Panel: 500 cd/m2	
	Contrast Ratio	1200:1 (standard Values)	
	Viewing Angle (CR > 10)	Horizontal: 178° (89°/89°)    Vertical: 178° (89°/89°)	
	Video Input Format	RGB Analog Signal/ Digital Signal	
	Video Input Interface	DP / HDMI	
	Touch Screen Type	Capacitive Touch Screen	
Touch Screen Technical Parameter	Cover Glass	Tempered Glass 3mm	
	Transparency	87%	
	Hardness	7H	
	Interface	USB2.0*2, USB Type B	
	Touch Point	10	
	Response Time	≤10 ms	
	Touch Method	Finger / Capacitive Pen	
	Touch Lifespan	≥50,000,000	
	Linearity	< 2%	
	Single-point OS	Windows XP , Linux	
	Multi-point OS	Windows7/8/10 , Android	
	Boundary Dimension	1007.10mm x 595.30mm x58.1mm	
	OSD Panel	Power switch、Menu、Up、Auto、Down	
	Power Supply	Input : ACC 220V±5%	
Touch Monitor Technical Parameter	Power Consumption	Max : 95w	
	Installation	Side Mounting Bracket,vesa	
	Accessory (Optional)	Signal Line	HDMI 1.8m , male to male
		USB Wire	A male to B male , 1.8m
		Adaptor	
		Power Line	Power Line, 1.5m , Black
	Temperature	Operating: 0°C-40°C ;    Storage: -20°C-60°C	
	Humidity	Operating: 20%-80%;    Storage: 10%-90%	
	Operation Altitude	< 3000m	
	Warranty	1 year	
	IP rated	Front IP65	

