

21.5" P-cap Touch Monitor



Model	H2212PW-UH
Touch Technology	P-cap
Version	V 1.0





Open-frame Touch Monitor

Horsent develops H2212PW-UH open-frame multi-touch monitor for high traffic vertical applications, such as finance, gaming, industry, self-service terminal, etc. Applies high performance PCAP touch technology, offers excellent 10-point touch and tablet-like user experience.

The durable, light weighted, display module delivers image with high resolution and clarity, yet still low power consumption.

It features a special designed mounted-molded front bezel, enables perfect matched mounting to your kiosk with great dust&water resistance.



Features

- 10-point touch
- Slim bezel
- Firm sealing
- Accurate touch
- Compact design
- Easy to install
- Flush mounted



Applications

- ATM
- Tickets machine
- Vending machine
- Information terminal
- Gaming machine



Product Name		21.5 inch LCD Touch Monitor	
Product Model		H2212PW-UH	
LCD panel	Size	21.5 inch	
Technical Parameter	Aspect Ratio	16 : 9	
	Backlight Type	LED Backlight	
	Pixel Pitch	0.248mm x 0.248mm	
	Active Area	476.64mm x 268.11mm	
	Best Resolution	1920 × 1080 @ 60 Hz	
	Response Time	25 ms	
	Color	16.7million	
	Brightness	LCD Panel: 250 cd/m ²	
	Contrast Ratio	1000:1 (standard Values)	
	Viewing Angle (CR > 10)	Horizontal: 178° (89°/89°) Vertical: 178° (89°/89°)	
	Video Input Format	RGB Analog Signal/ Digital Signal	
	Video Input Interface	VGA / HDMI	
	Input Frequency	Horizontal: 30~82 Hz Vertical: 50~75 Hz	
	Power Consumption	≤16.55W	
Touch Screen	Touch Screen Type	Capacitive Touch Screen	
Technical Parameter	Cover Glass	2.4mm	
	Transparency	87%	
	Hardness	7H	
	Interface	USB2.0	
	Touch Point	10	
	Response Time	≤10ms	
	Touch Method	Finger / Capacitive Pen	
	Touch Lifespan	≥50,000,000	
	Linearity	< 2%	
	Single-point OS	Windows XP , Linux	
	Multi-point OS	Windows7/8/10/11 , Android	
Touch Monitor	Boundary Dimension	533.6mm × 320.6mm × 41.0mm	
	OSD Panel	Optional Accessory : Power switch、Menu、Up、Auto、Down	
	Power Supply	Input : DC 12V±5%	
	Power Consumption	Max : 30w; Sleep : 3w; Off : 2w	
	Installation	Side Mounting Bracket , VESA 75mm&100mm	
	Accessory (Optional)	Signal Line	VGA , HDMI , 1.5m/1.8m , male to male
		USB Wire	A male to B male , 1.8m
		Adaptor	WT1203000 ,12V/3.0A , 115mmx47mmx31mm, Length 1.0m, ϕ 2.5 , Black
		Power Line	CCC Power Line, 1.5m , Black
		Temperature	Operating: 0°C-40°C ; Storage: -20°C-60°C
	Humidity		Operating: 20%-80%; Storage: 10%-90%
	Operation Altitude		< 3000m
	Warranty		(1 year)





